

CIRCULAR CHART RECORDER



SPECIFICATIONS

- ◆ Highly Precise Sealed Potentiometer As A Feedback Element.
- ◆ Highly Precise & Accurate Synchronous Or Stepper Motors.
- ◆ Predefined Input Signal K, J, R, S, T Thermocouples, DC MA, DC MV, RTD (Length Compensated).
- ◆ Accuracy Level 0.5 % FSD.
- ◆ Chart Speed 1 Day Or 7 Day / Revolution Selectable (Stepper Motor). OR Fixed Speed Predefined 4Hrs, 8 Hrs, 12 Hrs, 24 Hrs, 7 Days One Of It (Synchronous Motor)
- ◆ Range Selectable Through Span-zero Adjustment By Source.
- ◆ Power Supply 110 VAC / 240 AC 50 Hz (Predefined) Chart Circular Disk Type.
- ◆ Predefined Built In Indicator Or Controller Single Set Point.
- ◆ Straight Line Recorder Having Pointer, Writing Pen On One Carriage For Better Response And Accuracy.
- ◆ Circular Chart Writing Widths 52.5mm, 100mm (100mm Dia. & 257mm Dia.).
- ◆ Easily Replaceable & Disposable Fiber Tip Pen.
- ◆ Time Vs Process Value Continuous Line Graph.

Deals In:-



KASSO



Panasonic
ideas for life



HIWIN
Motion Control and System Technology



M/s SONICS CONTROL SYSTEMS

310-315, 3rd Floor, Laxmi Tower, Azadpur Commercial Complex,
Azadpur, New Delhi-110033.

Mobile - 09868254254, 08459001208 Telefax- +91 11 47884753

Email - scs.shivaki@gmail.com, scs.shivaki@hotmail.com

WEBSITE: www.shivaki.in