

Temperature + Humidity Controller



New Model No. 9654-HB
Size Available In
96 X 96 MM

Size Available In

96 X 96 MM

Model No.

PID-HB-96

SPECIFICATIONS

- Microcontroller based, Double display
- Power Supply 220VAC
- Input 3.3VDC or RTD
- Control: PID or On/Off
- Range : RTD -50.0 To 400.0 C
 Humidity 0 To 100%
- Temperature As per range adjustable in set mode.
- Humidity As per range adjustable in set mode.
- Ct 1 To 60 for SSR output & 10 To 120 second for Relay output adjustable
- Auto tuning require for pb, It & dt value
- Hysteresis 0.2 or 2 To 25.0 C or 25 C adjustable as per range selection for RTD
- Delay 0 To 250 second adjustable for cooling control
- Err -display if Sensor break ,open & reverse.
- Relay trip if sensor breaks, connection open or connection reverse.
- Calibration Error correction by front key switch (No preset setting)

Deals In:-



KASSO



Panasonic
ideas for life



HIWIN
Motion Control and System Technology



M/s SONICS CONTROL SYSTEMS

310-315, 3rd Floor, Laxmi Tower, Azadpur Commercial Complex,
Azadpur, New Delhi-110033.

Mobile - 09868254254, 08459001208 Telefax- +91 11 47884753
Email - scs.shivaki@gmail.com, scs.shivaki@hotmail.com
WEBSITE: www.shivaki.in